



RECOMMEND P.C.B. LAYOUT  
TOP VIEW

### Material:

- 1.Body: PPS UL 94V-0 Rated, Color:Black;
- 2.Cover: LCP UL 94V-0 Rated, Color:Black;
- 3.Contact: Phosphor Bronze;
- 4.Contact Plating: Gold Plating Over Nickel on Contact Area, Tin Plating on Solder Tail.

### Specification:

- 1.Current Rating: 0.5 AMP. Max.;
- 2.Dielectric Withstanding Voltage: 500V AC R.M.S For One Minute;
- 3.Insulation Resistance: 1000 M Ohms Min. AT 500V AC;
- 4.Contact Resistance: 30 M Ohms Max.;
- 5.Operating Temperature: -25°C to +85°C;
- 6.Durability: 5000 Cycles.
- 7.Processing Temp: 260°C for 30~60 Seconds Max

115B-B X A 0-R  
1 2 3 4 5

- |                    |             |
|--------------------|-------------|
| 1.Type             | 3.Stand Off |
| B:8 Pin            | A:0mm       |
| 2.Contact Plating  | 4.Peg       |
| A:Gold Plating     | 0:w/peg     |
| B:15u"Gold Plating | 5.ROHS      |
| C:30u"Gold Plating |             |

UNLESS OTHERWISE SPECIFIED TOLERANCE	
ANG.	±5°
0.	±
.0	±0.25
.00	±0.20

SCALE: AS SHOWN UNIT: mm

DRAWN 2007/5/4

CHECKED / /

APPROVED / /

SIZE A4 REV.

DRAWN NAME: SIM Card Socket Hinge type

PRODUCT NO. 115B-BXA0-R

FILE NAME: 115B-BXA0-R

REV.	DESCRIPTION	DATE	SIZE	REV.
1			A4	
2				
3				
4				
5				
6				
7				
8				
9				
10				