



RECOMMEND P.C.B LAYOUT  
TOLERANCE  $\pm 0.05$   
TOP VIEW

115G-A A A A-R  
1 2 3 4 5

- 1.Type A:6 Pin
- 2.Contact Plating A:Gold Plating
- 3.Stand Off A:0mm
- 4.Peg A:w/o peg
- 5.RoHS

MATERIALS  
1.HOUSING:HI-TEMP.(UL 94V-0).BLACK.  
2.TERMINAL:COPPER ALLOY(T=0.15mm).GOLD PLATED OVER NICKEL.  
3.COVER:STAINLESS STEEL(T=0.2mm)  
SPECIFICATION  
1.CURRENT RATING:1.0 A. MAX  
2.DIELECTRIC WITHSTANDING VOLTAGE: 500V AC R.M.S. FOR ONE MINUTE.  
3.INSULATION RESISTANCE:1000M $\Omega$  MIN. AT 500V DC.  
4.CONTACT RESISTANCE: 30m $\Omega$  MAX  
5.OPERATING TEMPERATURE: -40°C TO +85°C

NO.	DESCRIPTION	MATERIAL	COLOR	REMARK
③	SHELL	STAINLESS STEEL		
②	CONTACT	COPPER ALLOY	GOLD	
①	HOUSING	HI/TEMP	BLACK	

UNLESS OTHERWISE SPECIFIED TOLERANCE	
ANG.	$\pm 5$
0.	$\pm 0.3$
.0	$\pm 0.25$
.00	$\pm 0.20$
SCALE:	AS SHOWN
UNIT:	mm
DRAWN	2008/11/19
CHECKED	/ /
APPROVED	/ /

DRAWN NAME:  
SIM Card Socket  
H=1.8mm Hinge Type  
PRODUCT NO. 115G-AAAA-R  
FILE NAME: 115G-AAAA-R

REV.	DESCRIPTION	DATE	SIZE	REV.
			A4	