

**СУПЕР ЯРКИЕ СВЕТОДИОДЫ. Размер 2x5 мм, 5 мм, 5мм.**

Type	Part Number	Emitting Color	Chip Material	Lens - color	Wave Length (nm)	Luminous Intensity (mcd) @ If = 10mA Min. Max.	Operating & Storage Temp.(°C) Range	View Angle (deg) 2θ 1/2	Package Dimension Tolerance: ±0.25 (0.01) Unit: mm (inch)
------	-------------	----------------	---------------	--------------	------------------	---	-------------------------------------	-------------------------	---

2x5mm/Rectangular	2R53SDA-9	Red	GaAlAs	Red Diffused	660	175 ~ 250	-40 ~+85	120	
	2R53SDB-9	Red	GaAlAs	Red Diffused	660	250 ~ 350	-40 ~+85	120	
	2R53SCA-9	Red	GaAlAs	Water Clear	660	600 ~ 900	-40 ~+85	40	
	2R53SCB-9	Red	GaAlAs	Water Clear	660	900 ~ 1100	-40 ~+85	40	
	2G53SD-9	Green	GaP	Green Diffused	568	30 ~ 50	-40 ~+85	120	
	2G53SC-9	Green	GaP	Water Clear	568	80 ~ 250	-40 ~+85	40	

5mm/Cylindrical	5R53SCA-10	Red	GaAlAs	Water Clear	660	600 ~ 900	-40 ~+85	125	
	5R53SCB-10	Red	GaAlAs	Water Clear	660	900 ~ 1100	-40 ~+85	125	
	5R3UC-10	Red	GaAlAs	Water Clear	660	1200 ~ 1400	-40 ~+85	125	
	5G3SC-10	Green	GaP	Water Clear	568	80 ~ 250	-40 ~+85	125	
	5Y3SC-10	Yellow	AlGaInP	Water Clear	590	1000 ~ 1500	-40 ~+85	125	

5mm/Oval	5R3SCBR2310	Red	GaAlAs	Water Clear	660	1300 ~ 1600	-40 ~+85	70/25	
	5R3UCR2310	Red	GaAlAs	Water Clear	660	2000 ~ 3500	-40 ~+85	70/25	
	5G3SCG2310	Green	GaP	Water Clear	568	100 ~ 300	-40 ~+85	70/25	
	5Y3SCY2310	Yellow	AlGaInP	Water Clear	590	2000 ~ 3500	-40 ~+85	70/25	