

СВЕТОДИОДЫ ЦИЛИНДРИЧЕСКИЕ 5.0 мм

LED LAMP SPECIFICATION

Type	Part Number	Emitting Color	Chip Material	Lens - color	Wave Length (nm)	Luminous Intensity (mcd) @ If = 10mA		Operating & Storage Temp.(°C) Range	View Angle (deg) 2θ 1/2	Package Dimension Tolerance: ±0.25 (0.01) Unit: mm (inch)
						Min.	Max.			

5mm/Cylindrical	5R3PD-19	Red	GaP	Red Diffused	700	0.4 ~ 3.5	-40 ~+85	100	
	5R3HD-19	High Red	GaAsP/GaP	Red Diffused	635	3.5 ~ 12.0	-40 ~+85	100	
	5O3HD-19	Orange	GaAsP/GaP	Orange Diffused	590	1.5 ~ 7.5	-40 ~+85	100	
	5G3HD-19	Green	GaP	Green Diffused	568	1.5 ~ 7.5	-40 ~+85	100	
	5Y3HD-19	Yellow	GaAsP/GaP	Yellow Diffused	590	1.5 ~ 7.5	-40 ~+85	100	

5mm/Cylindrical	5R3HC-18	High Red	GaAsP/GaP	Water Clear	635	3.5 ~ 12.5	-40 ~+85	125	
	5G3HC-18	Green	GaP	Water Clear	568	1.8 ~ 8.0	-40 ~+85	125	
	5Y3HC-18	Yellow	GaAsP/GaP	Water Clear	590	1.8 ~ 8.0	-40 ~+85	125	
	5R3HT-18	High Red	GaAsP/GaP	Red Transparent	635	3.5 ~ 12.5	-40 ~+85	125	
	5G3HT-18	Green	GaP	Green Transparent	568	1.8 ~ 8.0	-40 ~+85	125	
	5Y3HT-18	Yellow	GaAsP/GaP	Yellow Transparent	590	1.8 ~ 8.0	-40 ~+85	125	