

СВЕТОДИОДЫ КРУГЛЫЕ 8.0 - 10 мм

LED LAMP SPECIFICATION

| Type | Part Number | Emitting Color | Chip Material | Lens - color | Wave Length (nm) | Luminous Intensity (mcd) @ If = 10mA Min. Max. | Operating & Storage Temp.(°C) Range | View Angle (deg) 2θ 1/2 | Package Dimension Tolerance: ±0.25 (0.01) Unit: mm (inch) |
|------------|-------------|----------------|---------------|-----------------|------------------|---|-------------------------------------|-------------------------|---|
| 8mm/Round | 8R3PD-14 | High Red | GaAsP/GaP | Red Diffused | 635 | 22.0 ~ 100.0 | -40 ~+85 | 60 | |
| | 8O3HD-14 | Orange | GaAsP/GaP | Orange Diffused | 590 | 20.0 ~ 100.0 | -40 ~+85 | 60 | |
| | 8G3HD-14 | Green | GaP | Green Diffused | 568 | 18.0 ~ 80.0 | -40 ~+85 | 60 | |
| | 8Y3HD-14 | Yellow | GaAsP/GaP | Yellow Diffused | 590 | 18.0 ~ 80.0 | -40 ~+85 | 60 | |
| | 8R3HC-14 | High Red | GaAsP/GaP | Water Clear | 635 | 55.0 ~ 220.0 | -40 ~+85 | 40 | |
| | 8G3HC-14 | Green | GaP | Water Clear | 568 | 50.0 ~ 175.0 | -40 ~+85 | 40 | |
| | 8Y3HC-14 | Yellow | GaAsP/GaP | Water Clear | 590 | 50.0 ~ 175.0 | -40 ~+85 | 40 | |
| 10mm/Round | 10R3HD-15 | High Red | GaAsP/GaP | Red Diffused | 635 | 22.0 ~ 110.0 | -40 ~+85 | 60 | |
| | 10O3HD-15 | Orange | GaAsP/GaP | Orange Diffused | 590 | 22.0 ~ 110.0 | -40 ~+85 | 60 | |
| | 10G3HD-15 | Green | GaP | Green Diffused | 568 | 22.0 ~ 80.0 | -40 ~+85 | 60 | |
| | 10Y3HD-15 | Yellow | GaAsP/GaP | Yellow Diffused | 590 | 22.0 ~ 80.0 | -40 ~+85 | 60 | |
| | 10R3HC-15 | High Red | GaAsP/GaP | Water Clear | 635 | 60.0 ~ 250.0 | -40 ~+85 | 40 | |
| | 10G3HC-15 | Green | GaP | Water Clear | 568 | 60.0 ~ 250.0 | -40 ~+85 | 40 | |
| | 10Y3HC-15 | Yellow | GaAsP/GaP | Water Clear | 590 | 60.0 ~ 250.0 | -40 ~+85 | 40 | |